

30–40 HI Brewery

Standard Brewery
by Joh. Albrecht



Brewhouse

Annual output

Beer style

Control

Design

Energy supply

Power

Heating

Water

Installation area

Room size

Height

Floor load

Brew vessels

Value [Unit]

5000–30000 [hl]

All beer styles – infusion/decoction

Manual, semi and fully automatic

Stainless steel

70–100 [kW]

Gas 37,7 [m³/h]

10 [m³/h], ≥ 4 [bar]

800–1500 [m²]

≥ 5 [m]

2500 [kg/m²]

2–4

Additional modules for complete brewery

Our recommendation

Grist mill

2, 4 or 6 roller grist mill

Fermentation and Lagering

Tank type

Cylindro conical tank (CCT)

Tank size

40–80 [hl]

Insulation

Insulated or non-insulated

CIP cleaning

Manual – lost cleaning or
fully automatic – recuperation system

Yeast handling

Cooled yeast tubs, yeast propagation

Hot/Cold water handling

Lost or recuperation system

Filter

Cartridge filter or kieselgur filter

Filling

Bottles

Filling line with 500 bottles/h up to
1000 bottles/h (semi-automatic)

KEG cleaning and filling machine,
30 KEG/h (semi-automatic)

KEG

Standard Drawing of 30–40 hl Module Brewery by Joh. Albrecht

